

## Poly Tough Cart

Please follow all assembly and safety instructions to ensure proper use of the Poly Tough Cart.

Cart Components:	Qty:
¾" Bolts	4
1½" Bolts	8
Nylon Lock Nuts	12
Poly Tub	1
Handle	1
Frame with Axle	1
U-shaped Legs	2
Wheels	2
Cotter Pins	2

### Tools required for assembly:

Adjustable wrench  
Pliers

### Assembly Instructions

**Step 1.** Invert the Poly Tub and lay it on the ground or a flat surface. Continue with Steps 2 through 5 using the illustration below.

**Step 2.** Place the Frame with Axle on the Tub, lining up the holes in the Frame with the four holes in the bottom of the Tub. Insert a ¾" Bolt (bolt not shown) into each hole from underneath and tighten with a Nylon Lock Nut on top of the Frame. To make this step easier, have a second person hold the Tub and Frame together on it's side while you insert the bolts from underneath. Tighten each Lock Nut with an adjustable wrench.

**Step 3.** Attach the U-shaped Legs to the Frame using two 1½" Bolts and Nylon Lock Nuts per leg. Insert each bolt from the outer sides of the Frame and tighten with a Lock Nut inside the frame.

**Step 4** Attach the Handle to the Frame using two 1½" Bolts and Nylon Lock Nuts per side.

**Step 5.** Slide a Wheel onto each end of the Axle. Insert a Cotter Pin through small hole in each end of the Axle. Use pliers to spread the ends of the Cotter Pins to a wide "Y" to secure the Wheels to the Axle.

### Safety Precautions

- Do not carry passengers in this cart or allow children to play with the cart at any time.
- Use caution on slopes, especially when carrying heavy loads. The cart does not have brakes and may roll away from you.
- Do not exceed the 300-pound load recommendation for this cart.
- Distribute weight evenly when loading the cart. Too much weight in the front of the cart can cause the cart to flip up or roll unexpectedly and cause injury.

### Cart Maintenance

- Protect your cart from harsh weather by storing it in a shed, garage, or under a tarp when not in use.
- To keep the cart in proper working condition, tighten the nuts and bolts periodically.

