

Deck Tiles

Strength, durability and natural weather resistance have made teak the wood of choice for generations of builders and craftsmen. These Deck Tiles are made from dense teak heartwood that's harvested on a sustainable, environmentally-sound plantation in Costa Rica. They will last 10 to 20 years, weathering to silver-gray over time.

Deck Tiles are great for creating pathways, covering a concrete patio, or making a platform for your rain barrel. An interlocking plastic grid backing lets you connect the Tiles, using a rubber mallet.

Assembly

Step 1. Ground Installation

If you are installing Deck Tiles on a lawn, remove the sod and level the soil. To discourage weeds from growing through the Tiles, we recommend covering the soil with a landscape fabric, such as our Weed Shield® (item #36-551).

Step 2. Connect the interlocking plastic grids along the edge of each Tile. It is easiest to connect the Tiles by sliding the grid edge of one Tile up through the bottom of the grids on the second Tile. Lay the connected Tiles on the ground and tap them with a rubber mallet until level.

Step 3. For a more finished look after installation, you can use a hack saw to cut off the plastic



grids around the perimeter of the Tiles.

Teak Care Information: Wood is a natural material and its appearance will change when left outdoors. Ultraviolet radiation from the sun bleaches out ALL wood regardless of the species. We recommend using a mild detergent, such as Simple Green and water to clean and refresh the color of your teak wood. Add a little bleach if there is any mold or mildew.

Simple Green is available in most supermarkets and is a mild, non-toxic, non-abrasive and biodegradable cleaner that is good for removing grit, dust, or pollen. It also helps to keep the finish uniform in color and smooth. However, if after several years your teak has turned silver and you want to restore the original golden teak color, the best way to achieve this is by light sanding.